



Part No.	Colour	Wave Length	Lens Colour	Luminous Intensity(mcd)	Voltage(V)	Current(mA)	Deg
KTL030DWI	Red	700	White Diffused	8-15	1.7-2.4	20	80°
KTL030CWI	Red	645		40-80	1.7-2.4	20	80°
KTL030AWI-S	Red	630		100-200	1.7-2.4	20	80°
KTL030AWI-U	Red	640		300-400	1.7-2.4	20	80°
KTL030AWI-T	Red	623		500-800	1.7-2.4	20	80°
KTL030KWI	Green	572	White Diffused	6-10	1.7-2.4	20	80°
KTL030JWI	Green	572		30-40	1.7-2.4	20	80°
KTL030JWI-S	Green	572		100-200	1.7-2.4	20	80°
KTL030JWI-U	Green	572		200-400	1.7-2.4	20	80°
KTL030IWI	Yellow	590	White Diffused	100-200	1.7-2.4	20	80°
KTL030IWI-S	Yellow	590		200-400	1.7-2.4	20	80°
KTL030IWI-U	Yellow	590		400-800	1.7-2.4	20	80°
KTL030IWI-T	Yellow	590		800-1200	1.7-2.4	20	80°
KTL030FWI	Orange	610	White Diffused	80-100	1.7-2.4	20	80°
KTL030FWI-S	Orange	610		300-400	1.7-2.4	20	80°
KTL030FWI-U	Orange	610		400-800	1.7-2.4	20	80°
KTL030BGWI	Blue-Green	510	White Diffused	3000-4000	3.0-3.6	20	80°
KTL030BGWI-U	Blue-Green	510		4000-5000	3.0-3.6	20	80°
KTL030BLWI	Blue	470	White Diffused	400-600	3.0-3.6	20	80°
KTL030BHWI	Blue	470		600-1000	3.0-3.6	20	80°
KTL030BUWI	Blue	470		1000-1500	3.0-3.6	20	80°
KTL030PGWI	Pure Green	525	White Diffused	1500-2000	3.0-3.6	20	80°
KTL030PGWI-S	Pure Green	525		6000-7000	3.0-3.6	20	80°
KTL030PGWI-U	Pure Green	525		7000-8000	3.0-3.6	20	80°
KTL030WWI	White	----	White Diffused	1000-2000	3.0-3.6	20	80°
KTL030WHWI	White	----		2000-3000	3.0-3.6	20	80°
KTL030WUWI	White	----		3000-4000	3.0-3.6	20	80°