



Part No.	Colour	Wave Length	Lens Colour	Luminous Intensity(mcd)	Voltage(V)	Current(mA)	Deg
KTL056DDI	Red	700	Red Diffused	6-10	1.7-2.4	20	60/120°
KTL056CDI	Red	645		50-100	1.7-2.4	20	60/120°
KTL056ADI-S	Red	630		200-300	1.7-2.4	20	60/120°
KTL056ADI-U	Red	640		300-500	1.7-2.4	20	60/120°
KTL056ADI-T	Red	623		500-1000	1.7-2.4	20	60/120°
KTL056KDI	Green	572	Green Diffused	6-8	1.7-2.4	20	60/120°
KTL056JDI	Green	572		50-100	1.7-2.4	20	60/120°
KTL056JDI-S	Green	572		400-600	1.7-2.4	20	60/120°
KTL056JDI-U	Green	572		600-800	1.7-2.4	20	60/120°
KTL056IDI	Yellow	590	Yellow Diffused	200-300	1.7-2.4	20	60/120°
KTL056IDI-S	Yellow	590		500-800	1.7-2.4	20	60/120°
KTL056IDI-U	Yellow	590		800-1200	1.7-2.4	20	60/120°
KTL056IDI-T	Yellow	590		1200-1500	1.7-2.4	20	60/120°
KTL056FDI	Orange	610	Orange Diffused	200-300	1.7-2.4	20	60/120°
KTL056FDI-S	Orange	610		500-700	1.7-2.4	20	60/120°
KTL056FDI-U	Orange	610		700-1200	1.7-2.4	20	60/120°
KTL056BGDI	Blue-Green	510	Green Diffused	2000-3000	3.0-3.6	20	60/120°
KTL056BGDI-U	Blue-Green	510		3000-4000	3.0-3.6	20	60/120°
KTL056BLDI	Blue	470	Blue Diffused	500-1000	3.0-3.6	20	60/120°
KTL056BHDI	Blue	470		1000-1200	3.0-3.6	20	60/120°
KTL056BUDI	Blue	470		1200-1500	3.0-3.6	20	60/120°
KTL056PGDI	Pure Green	525	Green Diffused	3000-4000	3.0-3.6	20	60/120°
KTL056PGDI-S	Pure Green	525		4000-5000	3.0-3.6	20	60/120°
KTL056PGDI-U	Pure Green	525		5000-6000	3.0-3.6	20	60/120°
KTL056WDI	White	-----	White Diffused	1000-1500	3.0-3.6	20	60/120°
KTL056WHDI	White	-----		1500-1700	3.0-3.6	20	60/120°
KTL056WUDI	White	-----		1700-2000	3.0-3.6	20	60/120°