



Part No.	Colour	Wave Length	Lens Colour	Luminous Intensity(mcd)	Voltage(V)	Current(mA)	Deg
KTL056DWI	Red	700	White Diffused	6-10	1.7-2.4	20	70/95°
KTL056CWI	Red	645		50-100	1.7-2.4	20	70/95°
KTL056AWI-S	Red	630		200-300	1.7-2.4	20	70/95°
KTL056AWI-U	Red	640		300-500	1.7-2.4	20	70/95°
KTL056AWI-T	Red	623		500-1000	1.7-2.4	20	70/95°
KTL056KWI	Green	572	White Diffused	6-8	1.7-2.4	20	70/95°
KTL056JWI	Green	572		50-100	1.7-2.4	20	70/95°
KTL056JWI-S	Green	572		400-600	1.7-2.4	20	70/95°
KTL056JWI-U	Green	572		600-800	1.7-2.4	20	70/95°
KTL056IWI	Yellow	590	White Diffused	200-300	1.7-2.4	20	70/95°
KTL056IWI-S	Yellow	590		500-800	1.7-2.4	20	70/95°
KTL056IWI-U	Yellow	590		800-1200	1.7-2.4	20	70/95°
KTL056IWI-T	Yellow	590		1200-1500	1.7-2.4	20	70/95°
KTL056FWI	Orange	610	White Diffused	200-300	1.7-2.4	20	70/95°
KTL056FWI-S	Orange	610		500-700	1.7-2.4	20	70/95°
KTL056FWI-U	Orange	610		700-1200	1.7-2.4	20	70/95°
KTL056BGWI	Blue-Green	510	White Diffused	2000-3000	3.0-3.6	20	60/80°
KTL056BGWI-U	Blue-Green	510		3000-4000	3.0-3.6	20	60/80°
KTL056BLWI	Blue	470	White Diffused	500-1000	3.0-3.6	20	60/80°
KTL056BHWI	Blue	470		1000-1200	3.0-3.6	20	60/80°
KTL056BUWI	Blue	470		1200-1500	3.0-3.6	20	60/80°
KTL056PGWI	Pure Green	525	White Diffused	3000-4000	3.0-3.6	20	60/80°
KTL056PGWI-S	Pure Green	525		4000-5000	3.0-3.6	20	60/80°
KTL056PGWI-U	Pure Green	525		5000-6000	3.0-3.6	20	60/80°
KTL056WWI	White	----	White Diffused	1000-1500	3.0-3.6	20	60/80°
KTL056WHWI	White	----		1500-1700	3.0-3.6	20	60/80°
KTL056WUWI	White	----		1700-2000	3.0-3.6	20	60/80°