



Part No.	Colour	Wave Length	Lens Colour	Luminous Intensity(mcd)	Voltage(V)	Current(mA)	Deg
KTL05DDTI	Red	700	Red Transparent	4-6	1.7-2.4	20	140°
KTL05DCTI	Red	645		15-25	1.7-2.4	20	140°
KTL05DATI-S	Red	630		60-100	1.7-2.4	20	140°
KTL05DATI-U	Red	640		100-200	1.7-2.4	20	140°
KTL05DATI-T	Red	623		200-400	1.7-2.4	20	140°
KTL05DKTI	Green	572	Green Transparent	10-20	1.7-2.4	20	140°
KTL05DJTI	Green	572		20-50	1.7-2.4	20	140°
KTL05DJTI-S	Green	572		80-150	1.7-2.4	20	140°
KTL05DJTI-U	Green	572		200-300	1.7-2.4	20	140°
KTL05DITI	Yellow	590	Yellow Transparent	80-120	1.7-2.4	20	140°
KTL05DITI-S	Yellow	590		120-200	1.7-2.4	20	140°
KTL05DITI-U	Yellow	590		200-300	1.7-2.4	20	140°
KTL05DITI-T	Yellow	590		300-400	1.7-2.4	20	140°
KTL05DFTI	Orange	610	Orange Transparent	40-80	1.7-2.4	20	140°
KTL05DFTI-S	Orange	610		120-200	1.7-2.4	20	140°
KTL05DFTI-U	Orange	610		200-300	1.7-2.4	20	140°
KTL05DBGTI	Blue-Green	510	Green Transparent	300-400	3.0-3.6	20	140°
KTL05DBGTI-U	Blue-Green	510		400-800	3.0-3.6	20	140°
KTL05DBLTI	Blue	470	Blue Transparent	100-200	3.0-3.6	20	140°
KTL05DBHTI	Blue	470		200-300	3.0-3.6	20	140°
KTL05DBUTI	Blue	470		300-400	3.0-3.6	20	140°
KTL05DPGTI	Pure Green	525	Green Transparent	500-800	3.0-3.6	20	140°
KTL05DPGTI-S	Pure Green	525		800-1200	3.0-3.6	20	140°
KTL05DPGTI-U	Pure Green	525		1200-1500	3.0-3.6	20	140°
					150-250		
				250-400			140°
				400-500			140°