



Part No.	Colour	Wave Length	Lens Colour	Luminous Intensity(mcd)	Voltage(V)	Current(mA)	Deg
KTL05SDCI	Red	700	Water Clear	10-15	1.7-2.4	20	50/130°
KTL05SCCI	Red	645		80-150	1.7-2.4	20	50/130°
KTL05SACI-S	Red	630		500-1000	1.7-2.4	20	50/130°
KTL05SACI-U	Red	640		1000-1500	1.7-2.4	20	50/130°
KTL05SACI-T	Red	623		1500-2000	1.7-2.4	20	50/130°
KTL05SKCI	Green	572	Water Clear	6-10	1.7-2.4	20	50/130°
KTL05SJCI	Green	572		100-150	1.7-2.4	20	50/130°
KTL05SJCI-S	Green	572		1000-1500	1.7-2.4	20	50/130°
KTL05SJCI-U	Green	572		1500-2500	1.7-2.4	20	50/130°
KTL05SICI	Yellow	590	Water Clear	400-600	1.7-2.4	20	50/130°
KTL05SICI-S	Yellow	590		500-1000	1.7-2.4	20	50/130°
KTL05SICI-U	Yellow	590		1000-2000	1.7-2.4	20	50/130°
KTL05SICI-T	Yellow	590		2000-3000	1.7-2.4	20	50/130°
KTL05SFCI	Orange	610	Water Clear	600-800	1.7-2.4	20	50/130°
KTL05SFCI-S	Orange	610		1500-2500	1.7-2.4	20	50/130°
KTL05SFCI-U	Orange	610		2500-3500	1.7-2.4	20	50/130°
KTL05SBGCI	Blue-Green	510	Water Clear	5000-7000	3.0-3.6	20	30/80°
KTL05SBGCI-U	Blue-Green	510		7000-9000	3.0-3.6	20	30/80°
KTL05SBLCI	Blue	470	Water Clear	1500-2500	3.0-3.6	20	30/80°
KTL05SBHCI	Blue	470		2500-3500	3.0-3.6	20	30/80°
KTL05SBUCL	Blue	470		3000-4000	3.0-3.6	20	30/80°
KTL05SPGCI	Pure Green	525	Water Clear	8000-9000	3.0-3.6	20	30/80°
KTL05SPGCI-S	Pure Green	525		9000-10000	3.0-3.6	20	30/80°
KTL05SPGCI-U	Pure Green	525		10000-12000	3.0-3.6	20	30/80°
KTL05SWCI	White	-----	Water Clear	3000-4000	3.0-3.6	20	30/80°
KTL05SWHCI	White	-----		4000-5000	3.0-3.6	20	30/80°
KTL05SWUCI	White	-----		5000-6000	3.0-3.6	20	30/80°